

# Cherishmet Inc.

301 Route 17, Suite 800, Rutherford, NJ 07070 USA  
Web site: <http://www.cherishmet.com>



Telephone: (201) 842-7612  
Facsimile: (201) 455-6816  
Toll Free: (866) 804-0083

## Pellet Carbon for Air Purification

Model: VG Grade Activated Carbons for Air Purification

### Application:

VG grade carbon is a virgin anthracite coal based activated carbon. It is palletized in form. It is mainly used for purification of chemical materials' gases, carbon dioxide gas in beverage making and other gases like hydrogen, nitrogen chlorine, hydrochloride, ethylene, cracked gas and inert gases. It is for purification, specification and refinement of exhaust from automatic installation.

### Specification:

Spec Type	Moisture Content (%) Max.	Hardness (%) Min.	Ash Content (%) Max.	C.T.C. Absorption (%) Min.	Apparent Density (g/l)	Diameter (mm)
VG-2050	3	95	8	50	580 +/- 20	2.0
VG-2060	3	95	10	60	530 +/- 20	2.0
VG-2070	3	95	10	70	510 +/- 20	2.0
VG-3050	3	95	10	50	540 +/- 20	3.0
VG-3060	3	95	10	60	510 +/- 20	3.0
VG-3070	3	95	12	70	500 +/- 20	3.0
VG-4050	3	95	10	50	530 +/- 20	4.0
VG-4060	3	95	10	60	510 +/- 20	4.0
VG-4070	3	95	10	70	490 +/- 20	4.0
VG-5060	3	95	10	60	500 +/- 20	5.0

### Packing:

Material to be packed in black super sacks with 500KG or 1100LB net each, 2 sacks per pallet. 20 – 25KG small bags are available.

### Remarks:

The above specification can be adjusted in accordance with the customer's requirement.